



Klents

FK 5-1-12

eKö
System

360° protection

When the most important thing is that the business does not stop

The care and respect for the environment of the FK 5-1-12 extinguishing agent is the best among chemical fire protection agents.

In addition, it is harmless to people and to all equipment within the protected space as it has a low design concentration, is dielectric and evaporates 50 times faster than water.

Its operation is based on reducing the temperature of the fire, eliminating one of the basic elements of the fire tetrahedron.

Thanks to its 50 bar working pressure, it is ideal for the use of selector valves and main and reserve systems. Allows longer pipe runs and protects rooms that are far apart from the cylinder storage location.



Certificates



Applications

Archives y Libraries
Museums and Heritage
Health and Pharmacy
Laboratories and Clean Rooms
Data Centers
Communications
Control Rooms
Electrical Rooms
Substations
Transformers
Oil & Gas
Mines and Extraction
Military

Great Advantages

It is ideal for use in total flooding and local application applications.

Without any type of residue, with an evaporation capacity 50 times faster than water.

It is not corrosive and it is not a conductor of electricity, nor does it generate condensation or humidity.

Suitable for land, sea and air transport.

It is stored in liquid form and is discharged as a gas at low pressure.

Saves space by storing as a liquid: requires fewer storage cylinders.

It adapts to any risk with the different cylinder sizes available.

ISO 9001 quality system.

Klents

23 Poeta Joan Maragall St. 28020 Madrid, Spain
+34 910 054 660
www.klents.com | info@klents.com